

Version 1.0 Revision Date 09/2017 Page 1/11

SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

Blaze Products Corporation urges the customer receiving this Safety Data Sheet (SDS) to study it carefully to become aware of hazards, if any, of the product involved. In the interest of safety, you should: (1) notify your employees, agents, and contractors of the information on this sheet, and (2) furnish a copy to each of your customers to inform their employees and customers as well.

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY UNDERTAKING

1.1. Product identifier

Product name Blaze Jelled Methanol Chafing Dish Fuel

All Blaze GB Series Methanol Fuel

Synonym(s) Jelled Methanol (*Limited Quantity*)

GB200 Flammable Solids, Organic, N.O.S. (contains jelled Methanol)

CAS number 67-56-1

EC number

Index number

REACH Registration number

1.2. Relevant identified uses of the substance and uses advised against

Applications A jelled alcohol fuel for warming food, in chafing dishes only.

The fuel is jelled Methanol. Keep out of reach of children and pets.

1.3. Details of the supplier of the safety data sheet

Name BLAZE Products Corporation

Address P. O. Box 1409

Shelbyville, Kentucky 40066-1409

Telephone (502) 633-0650

Contact Chemtrec 1-800-424-9300 or 703-527-3887

1.4. Emergency telephone number

Telephone <u>USA</u>: 24 hr Emergency Assistance: 1-800-424-9300 day or night

Outside the continental United States: 1-703-527-3887 (collect calls

accepted). (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1.1. Classification of the mixture according to the directive 1999/45/EEC (DPD)

Flam. Sol. 1 H228 Flammable Solid

T; TOXIC TOXIC: Danger of very serious irreversible effects, such as blindness through

inhalation, in contact with skin and if swallowed.

2.1.2. Classification of the mixture according to the regulation (EC) no. 1272/2008 (CLP)

Flam. Sol. 1 H228 Flammable Solid
Acute Tox. 3 H301 Toxic if swallowed
Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.

STOT SE1 H370 Causes damage to organs.



Version 1.0 **Revision Date** 09/2017 Page 2/11

SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

2.2. Label elements according to the regulation (EC) no. 1272/2008 (CLP)

Hazard pictograms

GHS 02 Flame

Danger

GHS 06 Skull & crossbones

GHS 08 Health Hazard

Signal word

Hazard statements

GHS02 Danger GHS06 Acute Toxic 3

GHS08 Health Hazard (causes damage to organs)

H228 Flammable Solid H301 Toxic if swallowed H311 Toxic in contact with skin

H331 Toxic if inhaled H370 Health Hazard

Precautionary statements

- Prevention

P101 If medical advice is needed, have product container or label on hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fumes/gas/mist/vapors/spray.

Precautionary statements

- Response

P301 + P310 If swallowed: immediately call a poison center (1-800-222-

1222) or a doctor/physician.

P303 + P361 + P353 If on skin or hair: Remove/take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304 + P340 If inhaled: Move victim to fresh air and keep at rest in a position

comfortable for breathing.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if worn and easy to do. Continue rinsing.

P307 + P311 If exposed: Call a poison center or doctor/physician.

P370 + P378 In case of fire, use for extinguishing: C02, powder or water

spray.

Precautionary statements

- Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

P233 Keep container tightly closed.

Precautionary statements

- Disposal

P501 Dispose of contents/container as hazardous or special waste in

accordance with local and national regulations.





2.3. Other hazards

WHMIS symbols:



B4 - Flammable Solid.



D1A – Very toxic material causing immediate or serious toxic affects.



D2A – Very toxic material causing other toxic affects.



SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS-Nr.	EC-Nr.	Index-Nr.	[%]	Classification DSD/CLP	Specific concentrations limit
Methanol	67-56-1	200-659-6	603-001-00-X	<74.8	Flam. Liq 2; H225 Acute Tox. 3; H331 Acute Tox. 3; H311 Acute Tox. 3; H301	STOT SE 1; H370: C = 10 % STOT SE 2; H371: 3 % = C < 10 % STOT SE 1; H370

Acetone	67-64-1	200-662-2	606-001-00-8	Trace	
					-
Denatonium Benzoate	3734-33-6	223-095-2	-	Trace	-

4. FIRST AID MEASURES

4.1. Description of first aid measures

After eye contact Remove contact lenses if worn. Hold eye lids open and flush with water for

15 minutes. Call physician if irritation persists.

After skin contact Thoroughly wash exposed area with soap and water. Remove contaminated

clothing. Launder contaminated clothing before re-use. If skin irritation

continues, consult a doctor.

After inhalation Move individual to fresh air. In case of irregular breathing or respiratory

arrest, provide artificial respiration.

After ingestion If victim is conscious, rinse out mouth and give two glasses of water. Do not

induce vomiting. Call a physician or Poison Control Center: 1-800-222-1222 immediately. Never give anything by mouth to an unconscious person.

General Remark Any doubt, seek medical attention and show container label.

4.2. Most important symptoms and effects, both acute and delayed

See 4.1.

SWALLOWING: **TOXIC**. Can cause irreversible effects, such as blindness.

EYES: Can cause severe irritation, redness, tearing.

SKIN: Prolonged or repeated contact can cause moderate irritation, defatting and dermatitis.

BREATHING: Toxic by inhalation of vapors can cause nasal and respiratory irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Effects may be delayed. Administration of ethanol may inhibit metabolism.



Version 1.0 Revision Date 09/2017 Page 4/11

SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

5. FIREFIGHTING MEASURES

5.1. Extinguishing media In case of fire: Use water, water mist or carbon dioxide for

extinguishing.

5.2. Special hazards arising from the substance or

mixture

Closed cans that are exposed to flame and heat may erupt

scattering burning fragments.

5.3. Advice for fire-fighters Wear self-contained respiratory protective device. Wear fully

protective suit.

Additional Information Cool endangered receptacles with water spray.

Flash Point: Tag closed cup 54°F (12.2°C)

Ignition Temperature: 430°F

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipmentand emergency procedures
Keep away from fire and other ignition sources. Ventilate the area. Wear suitable protective clothing. No smoking.

6.2. Environmental precautionsDo not allow to enter sewers/surface of ground water.

6.3. Methods and material for containment and Ab

cleaning up

Absorb spilled material using paper, floor absorbents, or other

absorbent material.

6.4. Reference to other sectionsSee precautions in section 7 for information on safe handling.

See section 8 for information on personal protective equipment. See section 13 for disposal information.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling Keep away from fire and other ignition sources. Ventilate the

area. Take precautionary measures against static discharge. Use only non-sparking tools. Do not smoke. Handle in accordance to national and regional regulations.

7.2. Conditions for safe storage, including any

incompatibilities

Keep container tightly closed and store in a cool (40-120°F or 4-49°C), well-ventilated place. Keep away from heat/sparks/open flame/hot surfaces/direct sunlight. Keep cool. No smoking.

7.3. Specific end use(s)This is a jelled alcohol fuel for warming food in chafing dishes

only.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Compound TLV (units): Threshold Limit PEL: Permissible Exposure Limit

 Methanol
 200 ppm (skin)
 200 ppm (skin)

 Acetone
 1000 ppm
 1000 ppm



Version 1.0 Revision Date 09/2017 Page 5/11

SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

8.2. Exposure controlsRespiratory protection: Not required under normal conditions of use.

<u>Hand protection</u>: Not required under normal conditions of use. Wash hands with soap & water immediately after cleaning up spilled product or wear gloves to clean up area.

Eye protection: Not required under normal conditions of use.

Body protection: Not required under normal conditions of use.

<u>Hygiene measures</u>: Wash hands after handling products. *Not to be consumed*.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information of basic physical and chemical properties

Physical state Methanol Solid Jell

Colour Blue

Odour Alcohol odour

Odour threshold Not applicable

pH Not applicable

Freezing point Not applicable

Boiling point 77°F (170.6°C)

Flash point Tag Closed 54°F (12.2°C)

Flammability Flammable

Auto flammability 845.6°F (452°C)

Upper/lower flammability or

explosive limits

Not applicable

Explosive properties No

Oxidizing properties Not applicable

Vapour pressure Not applicable

% volatile by volume 98%

Vapour density (AIR = 1) Not applicable

Relative density Not applicable

Density Not applicable

Specific gravity (H2O=1)

at 80° F

Not applicable



Version 1.0 Revision Date 09/2017 Page 6/11

SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

Solubility in water Mostly soluble

Partition coefficient

(n-octanol/water)

Not applicable

Decomposition temperature Not applicable

Viscosity Not applicable

9.2. Other information

No other information

10. STABILITY AND REACTIVITY

10.1. Reactivity Generally stable

10.2. Chemical stabilityGenerally stable

10.3. Possibility of hazardous reactions Hazardous polymerisation will not occur

10.4. Conditions to avoid Heat, open flame, direct sunlight, *and consumption*.

10.5. Incompatible materials Strong oxidizers

10.6. Hazardous decomposition materialsNone known

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Likely routes of exposure: skin and eye contact and inhalation.

Symptoms: symptoms of persons exposed to this material include, headache, nausea, dizziness, drowsiness, and drying or defatting of skin.

Acute toxicity Inhalation: Rat LC_{LO} – 64000 ppm/4H

Intraperitoneal: Rat LD_{50} – 9540 mg/kg

Oral: Human LD_{LO} – 340 mg/kg Man LD_{LO} – 13 gm/kg Mouse LD_{50} – 870 mg/kg Rat LD_{50} – 5628 mg/kg

Intravenous: Mouse $LD_{50} - 5673$ mg/kg Subcutaneous: Mouse $LD_{50} - 9800$ mg/kg

Skin: Rabbit LD₅₀ – 20 gm/kg Unreported: Man LD₅₀ – 868 mg/kg

Skin corrosion/irritation Human (eyes) – 5ppm

Prolonged or repeated contact can cause moderate irritation,

defatting and dermatitis.

Serious eye damage/irritation Rabbit (eye) – 40 mg (moderate)

Can cause severe irritation, redness and tearing

Skin sensitization Rabbit $LD_{50} - 20 \text{ gm/kg}$ Unreported Man $LD_{Lo} - 868 \text{ gm/kg}$



Version 1.0 Revision Date 09/2017 Page 7/11

SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

Germ cell mutagenicity Not classified.

Carcinogenicity This product is not reported to have any carcinogenic affects.

Reproductive toxicity Not classified.

STOT-single exposure Not classified.

STOT-repeated exposure Not classified.

Aspiration hazard Not classified.

11.2. Other information

Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation.

Ingestion: Swallowing can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

12. ECOLOGICAL INFORMATION

12.1. Toxicity 96 hr. LC₅₀ – Lepomis macrochirus (bluegill) – 15,400 mg/l.

NOEC – oryzias latipes – 7.900 mg/l – 200 hr.

48 hr EC_{50} – Daphnia magna (waterflea) – 10,000 mg/l. 98 hr Growth inhibition EC_{50} – Scenedesmus Capricomutum

(algae) - 22,000 mg/l.

12.2. Persistence and degradabilityReadily biodegradable

12.3. Bioaccumulative potentialDoes not bioaccumulate. Partition coefficient (n-octanol/wate)

Log Pow - (-0.77)

12.4. Mobility in soil This product is not mobile in soil.

12.5. Results of PBT and vPvB assessment This substance is not considered to be persistent,

bisaccumulating nor toxic (PBT). This substance is not considered to be very persistent nor very bioaccumulating

(vPvB).

12.6. Other adverse effectsBiochemical Oxygen Demand (BOD): 600-1,120 mg/g

Chemical Oxygen Demand (COD): 1,420 mg/g

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods Recycling/disposal in a safe manner according to national and

regional regulations. Do not allow product to reach sewage

system.

13.2. List of CER codesAllocation of the waste code numbers according EC Directive

91/692/EEC must be realized under considerations of existing

sector specifics and processes.



Version 1.0 Revision Date 09/2017 Page 8/11

SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

14. TRANSPORT INFORMATION

Overland transport (ADR/RID)

River transport (ADN)

Sea transport (IMDG)

14.1. DOT Classification USA Domestic (All BLAZE GB Series except GB200) Consumer Commodity ORM-D

ORM-D

14.3. DOT Classification International (All BLAZE GB Series except GB200) UN1325, Flammable solid, organic, N.O.S. (contains jelled Methanol), 4.1., PG II, LTD.QTY



Marine pollutant: No Tunnel Restrictions: Code (E) Flashpoint: 12.2°C

14.2. DOT Classification USA & International for GB200 are over 1 kg.

UN1325, Flammable solid, organic, N.O.S. (contains jelled Methanol), 4.1.,PG II Emergency Guide #133



ADR, IMDG

Marine pollutant: No Tunnel Restrictions: Code (E) Flashpoint: 12.2°C

14.5. Environmental hazards

Marine pollutant: No

14.6. Special precautions for user

Warning; Flammable Solids

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Regulation Components present in this product at a level which could require reporting

under the statute (Section 313) are: Methanol (CAS 67-56-1): 74.8%



Version 1.0 Revision Date 09/2017 Page 9/11

SAFETY DATA SHEET For All Methanol Jelled Packages BLAZE JELLED METHANOL/GB Series CHAFING DISH FUEL

US Federal regulations 200 Proof Ethanol

SARA Section 311/312 Hazard Classes:

Fire hazard

Delayed (chronic health hazard Immediate (acute) hazard

Sara 313: Methanol (CAS 67-56-1) - 74.8%

TSCA Information:

All components in this product are in compliance with TSCA Inventory

Requirements.

CERCLA: Methanol has been designated as hazardous substance with an RQ of

5000 lbs.

15.2. Chemical safety assessment

International regulations Canada

Methanol (CAS 67-56-1)

Listed on the Canadian DSL (Domestic Substances List).

WHMIS Classification:

Class B Division 2 – Flammable Solid

Class D-1B: Toxic (acute effects), Class D-2B: Skin and eye irritant

EU-Regulations

Ethyl alcohol (64-17-5)

Listed on the EEC Inventory EINECS (European Inventory of Existing Commercial

Chemical Substances). (200-659-6)

Classification according to Regulation (EC) No. 1272/2008 (CLP): Not classified.

Classification according to Directive 67/548/EEC (DSD) or 1999/45/EC (DPD): Not

classified.

16. OTHER INFORMATION

16.1. Indications on the revision

SDS revised on 7/13/2015: Addition of all fields as required by regulations 1907/2006/EC and 453/2010/EC.

16.2. Abbreviations and acronyms used

ADN/ADNR: Regulations concerning the transport of dangerous substances in barges on inland waterways.

ADR/RID: European Agreement concerns the International Carriage of Dangerous Goods by Road/

Regulations concerning the international carriage of dangerous goods by rail.

CAS Nr.: Chemical Abstract Service Number

CERCLA: Comprehensive Environmental Response Compensation and Liability Act

CLP: Classification, Labeling and Packaging
DOT: US Department of Transportation (USA)



Version 1.0 Revision Date 09/2017 Page 10/11

DSD: Dangerous Substance Directive

DPD: Dangerous Preparation Directive

EC Nr.: European Commission Number

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

HMIS: Hazardous Material Identification System (USA)

IATA: International Air Transport Associations

IMDG: International Maritime Dangerous Goods code

NFPA: National Fire Protection Association (USA)

PBT: Persistent, Bioaccumulative, Toxic

TSCA: Toxic Substance Control Act
UN Nr.: United Nations Number

vPvB: very Persistent and very Bioaccumulative

WHMIS: Workplace Hazardous Materials Information System (Canada)

16.3. Key literature references and sources for data Vendor SDS

16.4. Methods of evaluation for the classification of Vendor SDS

mixtures

16.5. List of relevant R phrases, hazard statements, safety phrases and/or precautionary statements not listed in section 2

H phrases:

H328 Flammable Solid
H301 Toxic if swallowed
H311 Toxic in contact with skin
H331 Toxic if inhaled
H370 Causes damage to organs

This information is based on our present knowledge and is provided according to the relevant EC and national regulations. This information is intended as a characterization of the product in order to provide guidance for the relevant safety issues. However, this document does not provide any warranty, expressed or implied, regarding the properties of the product.

No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices and/or standard operation procedures listed on packaging & website.

www.blazeproducts.com